

# M0MPBF02

10-Port, 360 Degree, Small Cell Canister Antenna

## Kaelus Next Generation Base Station Antennas

- Innovative slotted disc antenna technology
- 5 GHz U-NII-1 Compliant @ 1 W Input




GENERAL	MB Y1/Y2	HB P1/P2	LAA O1
Frequency Range [MHz]	1695-2690	3300-4200	5150-5925
Gain Over All Tilts [dBi]	9.0	8.5	5.5
Polarization	X	X	X
Azimuth Beamwidth [°]	360	360	360
Electrical Downtilt [°]	10	2	2
Ports Per Band	4	4	2

## Specifications and Layouts

MECHANICAL SPECIFICATIONS	
Antenna Dimensions: Length, Diameter [inch mm]	25.2x10.0   640x254
Net Weight (Antenna) [lbs kg]	15.6   7.1
Connector Type	4.3-10 female
Connector Quantity	10
Connector Position	Bottom
Windload, Calculation* [mph km/h]	93.2   150
Windload, Maximum [lbf N]	19   85
Survival Wind Speed [mph km/h]	150   241.4
Radome Material	ASA
Radome Color [RAL]	7035 ( Light Gray )
Product Environmental Compliance	RoHS
Lightning Protection	DC Ground

\* According to EN 1991-1-4:2005+A 1:2010



# MOMPBF02

10-Port, 360 Degree, Small Cell Canister Antenna

ELECTRICAL SPECIFICATIONS	MB Y1/Y2					HB P1/P2	LAA O1
Frequency Range [MHz]	1695-1780	1850-1995	2095-2200	2300-2400	2496-2690	3300-4200	5150-5925
Gain, Average [dBi]	8.0	8.3	9.0	9.5	10.0	8.8	5.5
Azimuth Beamwidth [°]	360 (pseudo)					360 (pseudo)	360 (pseudo)
Elevation Beamwidth [°]	29.8 ±4.0					20.5 ±2.0	24.0 ±3.0
Electrical Downtilt [°]	10					2	2
Elevation Downtilt Deviation [°]	1	1	1	1	1	1	2
First Upper Side Lobe Suppression [dB]	17	17	17	17	17	16	15
Upper Side Lobe Suppression [dB]	15	15	15	15	15	15	15
Polarization [°]	±45					±45	±45
Impedance [Ω]	50					50	50
VSWR	< 1.5:1					< 1.5:1	< 1.5:1
Return Loss [dB]	< -14.0					< -14.0	< -14.0
Cross Polar Isolation [dB]	25					25	25
Interband Isolation [dB]	25					25	25
Passive Intermodulation (PIM) 3rd order, 2x20W [dBc]	< -153					< -150	-
Maximum Effective Power Per Port [W]	100					50	10

SHIPPING AND ORDER INFORMATION	
Packing Size: Length, Width, Depth [inch mm]	34x18x18   864x458x458
Shipping Weight [lbs kg]	25.0   11.4 MOMPBF02-V1-P

ENVIRONMENTAL COMPLIANCE	
ETSI EN300019-1-1 for Storage	Class 1.2
ETSI EN300019-1-2 for Transportation	Class 2.3
ETSI EN300019-1-4 for Environmental Conditions	Class 4.1E
Cold Temperature Survival [°F °C]	-40   -40
Hot Temperature Survival [°F °C]	140   60

ADDITIONAL ACCESSORIES (AVAILABLE TO ORDER)	
Side Pole/Wall Mount Kit (incl. cover)	KIT-000039-P
Top Pole Mount Kit [2.4-6.3 inch 60-160mm] (incl. cover)	KIT-000040-P
Top Pole Mount Kit [5.5-8.7 inch 140-220mm] (incl. cover)	KIT-000041-P



Network planning files and datasheet in NGMN XML formats are available on request by email.

Kaelus follows the definitions and recommendations per NGMN P-Basta version 11.1 ([www.ngmn.org](http://www.ngmn.org)) within parameters shown on this datasheet.

All specifications are subject to change without notice. Visit [www.kaelus.com](http://www.kaelus.com) for the most current data sheets..

