


M6BPMU01

3x, 10-Port, 65 Degree Ultra Wide Band Base Station Sector Antennas

Kaelus Next Generation Base Station Antennas

- Tri-sector Monopole.
- Innovative Ultra Wide Band Slotted Disc Antenna Technology.
- High Gain Over An Extended Tilt Range.
- Fully Integrated Remote Electrical Tilt, AISG Compatible.
- Each Sector Supports MIMO: 2x2 on Low Band and 4x4 on High Band.

GENERAL	LB R1	HB Y1	HB Y2	HB Y3	HB Y4
Frequency Range	694-960	1695-2690	1695-2690	1695-2690	1695-2690
Gain Over All Tilts [dBi]	16.1	15.7	15.0	15.7	15.0
Polarization	X	X	X	X	X
Azimuth Beamwidth [°]	65	65	65	65	65
Electrical Downtilt Range [°]	2-12	2-12	2-12	2-12	2-12
Ports Per Band	2	2	2	2	2



x3

Specifications and Layouts

MECHANICAL SPECIFICATIONS	
Antenna Dimensions: Length, Diameter[mm]	2730 x 485
Net Weight (Antenna) [kg]	100
Connector Type	4.3-10 Female
Connector Quantity Per Sector	10
Connector Position	Bottom
Wind Load, Calculation [km/h]	150
Wind Load, Maximum [N]	TBD
Survival Wind Speed [km/h]	200
Radome Material	GRP
Radome Colour [RAL]	7047
Product Environmental Compliance	RoHS
Lightning Protection	DC Ground
REMOTE ELECTRICAL TILT (RET) INFORMATION	
Type	Integrated, Non-Removable
Power Input	10 - 30V DC
Protocol	3GPP/AISG2.0
RET Interface	8-Pin DIN
RET Interface (Quantity)	2 (1 Male + 1 Female)

M6BPMU01

3x, 10-Port, 65 Degree Ultra Wide Band Base Station Sector Antennas

ELECTRICAL SPECIFICATIONS	LB R1			HB Y1/Y3					HB Y2/Y4					
Frequency Range [MHz]	694-790	790-862	880-960	1695-1880	1900-2025	2110-2170	2300-2500	2500-2690	1695-1880	1900-2025	2110-2170	2300-2500	2500-2690	
Gain, Average [dBi]	Min Tilt	15.4	16.0	16.5	14.5	14.8	15.6	16.4	16.6	13.8	14.1	14.9	15.7	15.9
	Mid Tilt	15.6	16.2	16.7	14.7	15.0	15.8	16.6	16.8	14.0	14.3	15.1	15.9	16.1
	Max Tilt	15.4	16.0	16.5	14.5	14.8	15.6	16.4	16.6	13.8	14.1	14.9	15.7	15.9
Gain, Over All Tilts [dBi]	15.5 ±0.5	16.1 ±0.5	16.6 ±0.5	14.6 ±0.5	14.9 ±0.5	15.7 ±0.5	16.5 ±0.5	16.7 ±0.5	13.9 ±0.5	14.2 ±0.5	15.0 ±0.5	15.8 ±0.5	16.0 ±0.5	
Azimuth Beamwidth [°]	69.0 ±3.0	66.0 ±3.0	63.0 ±2.0	66.0 ±6.0	68.0 ±4.0	64.0 ±3.0	61.0 ±4.0	59.0 ±3.0	66.0 ±6.0	68.0 ±4.0	64.0 ±3.0	61.0 ±4.0	59.0 ±3.0	
Elevation Beamwidth [°]	12.0 ±1.0	10.8 ±0.6	9.4 ±0.6	10.8 ±0.5	10.4 ±0.5	9.3 ±0.5	8.3 ±0.5	7.6 ±0.5	10.8 ±0.5	10.4 ±0.5	9.3 ±0.5	8.3 ±0.5	7.6 ±0.5	
Electrical Downtilt [°]	2-12			2x 2-12					2x 2-12					
Elevation Downtilt Deviation [°]	0.5	0.5	0.5	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	
Front-to-Back Ratio, Total Power, ±30° [dB]	23	24	22	23	23	23	23	23	23	23	23	23	23	
Cross Polar Discrimination Over Sector [dB]	10	11	10	8	10	12	8	8	8	10	12	8	8	
First Upper Side Lobe Suppression [dB]	16	17	17	17	17	17	17	17	17	17	17	17	17	
Upper Side Lobe Suppression [dB]	15	15	15	15	15	15	15	10	15	15	15	15	10	
Polarization [°]	±45			±45					±45					
Impedance [Ω]	50			50					50					
VSWR	< 1.5:1			< 1.5:1					< 1.5:1					
Return Loss [dB]	< -14.0			< -14.0					< -14.0					
Cross Polar Isolation [dB]	30			28					28					
Interband Isolation [dB]	35			35					35					
Passive Intermodulation [dBc]	< -153			< -153					< -153					
Maximum Effective Power Per Port [W]	350			350					350					

PRODUCT VARIANT	
Single RET Firmware Configuration	M6BPMU01-V1
Multi RET Firmware Configuration	M6BPMU01-V2

SHIPPING AND ORDER INFORMATION	
Packing Size: Length, Width, Depth [mm]	2800 x 550 x 550
No Bracket: Shipping Weight [kg], P/N	142 M6BPMU01-Vx-P1

ENVIRONMENTAL COMPLIANCE	
ETSI EN300019-1-1 for Storage	Class 1.2
ETSI EN300019-1-2 for Transportation	Class 2.3
ETSI EN300019-1-4 for Environmental Conditions	Class 4.1E
Cold Temperature Survival [°C]	-40
Hot Temperature Survival [°C]	60

Network planning files and datasheet in NGMN XML formats are available on request by email.

Kaelus follows the definitions and recommendations per NGMN P-Basta version 10.0 (www.ngmn.org) within parameters shown on this datasheet.

All specifications are subject to change without notice. Visit www.kaelus.com for the most current data sheets.

