

LOW PIM RF ADAPTORS

LOW PIM RF ADAPTORS

FEATURES

- Better than -122dBm with 2x20W (-165dBc) Performance
- Wide range of adaptors available to suit different connector configurations
- RoHS compliant



TECHNICAL SPECIFICATIONS

RF SPECIFICATIONS	
Passband	DC - 6GHz
Return loss	18dB
Intermodulation products	-165dBc with 2x20W
MECHANICAL	
Weight	0.05kg 0.1lb
Connectors	See ordering information

ORDERING INFORMATION

PART NUMBER	DESCRIPTION
R40-10100	7/16 (M) TO 4.3-10 (F)
R40-10101	7/16 (F) TO 4.3-10 (F)
R40-10114	7/16 (M) TO 4.3-10 (M)
R40-10111	7/16 (F) TO 4.3-10 (M)
R40-10102	4.3-10 (F) TO 4.3-10 (F)
R40-10106	4.3-10 (M) TO 4.3-10 (M)
R79-10093	7/16 (F) TO 7/16 (F)
R40-10054	7/16 (M) TO 7/16 (M)

OPTIONAL ACCESSORIES - SOLD SEPARATELY	
PART NUMBER	DESCRIPTION
R92-0459	Connector Cleaning Kit