


MI-172

TMA TWIN 1800/2100 4 BTS PORTS

Designed to be deployed in collocated 1800 and 2100 systems, the Kaelus MI-172 enhances cell uplink coverage in 1800 and 2100 through improved system noise figure, thereby saving operational and capital expenditure.

FEATURES

- Improved base station sensitivity through gain in the 1800 and 2100 uplink
- Internal diplexing on antenna port of 1800,2100 bands: 2 Antenna ports
- 4 BTS ports
- Excellent noise figure performance
- Full AISG operation and RET antenna support, AISG2.0 compatible
- Small and light for minimum visual impact



TECHNICAL SPECIFICATIONS

BAND NAME	1800	2100
DOWNLINK		
Passband	1805 - 1880MHz	2110 - 2170MHz
Insertion loss	0.65dB maximum	0.4dB maximum
Return loss	18dB minimum	
Maximum input power	200W (average)	200W (average)
Intermodulation products	-159dBc in RX band at ANT	-168dBc in RX band at ANT
UPLINK		
Passband	1710 - 1785MHz	1920 - 1980MHz
Gain	12dB nominal	
Return loss	16dB minimum	
Bypass return loss	12dB minimum	
Bypass loss	2.7dB maximum	2.5dB maximum
Noise figure	1.5dB maximum	1.4dB maximum
Output IP3	25dBm typical	
Maximum input power with no damage	12dB typical	
ELECTRICAL		
Impedance	50Ohms	
AISG MODE OF OPERATION (AUTO SELECTED ON VALID AISG 2.0 FRAMES)		
AISG signals can be applied to the BTS ports. The TMA unit switches to AISG mode when valid frames are detected on either port. Each LNA is controlled uniquely by its sub-unit number.		
DC supply voltage	24 V DC nominal (+9.0V to +31V DC)	
AISG version	2.0	
Power consumption, AISG mode	< 4W	
AISG connector, current rating	IEC60130-9, 8-pin female, 1.6A	

ENVIRONMENTAL	
For further details of environmental compliance, please contact Kaelus.	
Temperature range	-40°C to +65°C -40°F to +149°F
Ingress protection	IP67
Lightning protection	RF: ±5kA (8/20us), AISG: ±2.5kA (8/20us) common mode
MTBF	>1,000,000 hours
Compliance	EMC: EN 301 489-8/-23 Safety: IEC/EN 62368-1 Operation: ETSI EN 300 019-1-4 class 4.1E Storage: ETS 300 019-1-1 class 1.2



MECHANICAL	
Dimensions H x D x W	224 x 111 x 209 mm 8.8 x 4.4 x 8.2in (excluding brackets and connectors)
Weight	6.5kg 14.3lbs
Finish	Powder coated, NCS 1502-R
Connectors	See ordering information
Mounting	Pole/wall bracket using two metal clamps, suits 40-140mm diameter poles

SHIPPING INFORMATION	
Carton size	360 x 270 x 180mm 14.7 x 10.63 x 7.09in
Gross weight (including packaging)	7.2kg 15.8lb
Carton Qty / Pallet	48

ORDERING INFORMATION

PART NUMBER	CONFIGURATION	OPTIONAL FEATURES	CONNECTORS	AISG MODE
MI-17201	TWIN, 4 in / 2 out	BASE MODEL	7/16 (F) 1xAISG	COMMON MODE ONETWO (*)
MI-17202	TWIN, 4 in / 2 out	BASE MODEL	7/16 (F) 1xAISG	COMMON MODE TWOTWO (**)
MI-17206	TWIN, 4 in / 2 out	BASE MODEL	7/16 (F) 2xAISG	INDEPENDENT
MI-17231	TWIN, 4 in / 2 out	BASE MODEL	4.3-10 (F) 1xAISG	COMMON MODE ONETWO (*)
MI-17232	TWIN, 4 in / 2 out	BASE MODEL	4.3-10 (F) 1xAISG	COMMON MODE TWOTWO (**)
MI-17236	TWIN, 4 in / 2 out	BASE MODEL	4.3-10 (F) 2xAISG	INDEPENDENT
(*) ONETWO: the TMA is identified as 1 logic unit with 2 subunits				
(**) TWOTWO: the TMA is identified as 2 logic units with 2 subunits each				

ELECTRICAL BLOCK DIAGRAM



MECHANICAL BLOCK DIAGRAM

