

R92-0443

DUAL BATTERY CHARGING CRADLE

The Dual battery charging station for the convenience of charging 2 batteries simultaneously without interrupting current ongoing testing with portable PIM analyzer.



FEATURES

- Charges 2 batteries simultaneously
- LED status indicator

TECHNICAL SPECIFICATIONS

ELECTRICAL	
Supply Voltage	29.4V
Supply Current	1.2A
PRODUCT COMPATIBILITY	
Compatible with	Standard battery: R92-0287 High capacity battery: ASSY108321
MECHANICAL	
Dimensions H x D x W	50 x 135 x 190mm 2 x 5.3 x 7.5in approx
Weight	0.45kg 1lbs
ENVIRONMENTAL	
Operating temperature range	+10°C to +45°C +50°F to +113°F
Storage temperature range	-20°C to +60°C -4°F to +140°F
Operational humidity	5% to 90% non-condensing

ORDERING INFORMATION

PART NUMBER	DESCRIPTION
R92-0443	Dual Battery Charging Cradle
R92-0740	Bundle: Dual Battery Charging Cradle with AC adaptor and power cord.
OPTIONAL ACCESSORIES - SOLD SEPARATELY	
PART NUMBER	DESCRIPTION
R29-4382	AC Adaptor (also supplied with the Portable PIM analyzer)



Battery cradle charging two Standard batteries